

CLICK HERE TO JUMP TO USE DIRECTIONS

GORDON'S® PRUNING SEALER READY-TO-USE ALL-WEATHER TREE PAINT

Forms a protective seal for pruned or damaged trees, shrubs, and ornamentals.

KEEP OUT OF REACH OF CHILDREN CAUTION

See below for additional Precautionary Statements.



**READ THE ENTIRE LABEL FIRST.
OBSERVE ALL PRECAUTIONS AND
FOLLOW DIRECTIONS CAREFULLY.**

PRECAUTIONARY STATEMENTS

CAUTION: KEEP OUT OF REACH OF CHILDREN. Harmful or fatal if swallowed. Avoid breathing vapors. Avoid contact with eyes and skin.

IF IN EYES: Flush eyes thoroughly with fresh water.

IF ON SKIN: Wash with soap and water.

IF SWALLOWED: Consult a physician.

PHYSICAL-CHEMICAL HAZARDS

CAUTION: Contents under pressure. Do not use or store near heat or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

INSTRUCTIONS

GORDON'S PRUNING SEALER is an all-weather tree paint and wound dressing used to seal cuts, wounds, and grafts of trees, shrubs, and ornamentals. This asphalt emulsion provides a protective layer over pruned, grafted, or damaged surfaces and may prevent desiccation.

TO OPERATE — Shake before using. Hold the can upright with the valve 8 to 12 inches from the surface to be treated. Press the valve to spray. Apply uniformly, allow to dry, and make two applications. Spray away from buildings, sidewalks, fences, and painted surfaces to avoid staining.

SHADE TREES, FRUIT TREES, BROADLEAF SHRUBS, NEEDLED EVERGREENS

After pruning branches or trunks, apply GORDON'S PRUNING SEALER to the primary cuts or exposed wood and to the adjacent bark. Two applications are recommended.

GORDON'S PRUNING SEALER may be used at any time to seal wounds or to repair bark and limb damage. Trim as required and treat. Before banding and bracing split limbs, apply thoroughly.

ROSES, VINES, HERBACEOUS PLANTS, AND CONTAINER-GROWN ORNAMENTALS

After pruning rose canes, apply GORDON'S PRUNING SEALER to the exposed areas of the canes.

After trimming or pruning stems, limbs, or branches with diameters greater than ½ inch, apply GORDON'S PRUNING SEALER to the exposed wood and adjacent bark.

WOODEN PLANTERS, PLANTING TUBS, POTS AND OTHER PLANT CONTAINERS

Two applications of GORDON'S PRUNING SEALER are recommended to seal small holes and cracks in plant containers. To avoid staining, spray away from painted surfaces.

RAIN GUTTERS, RAIN SPOUTS, ROOF FLASHING, CONCRETE AND ASPHALT DRIVEWAYS

Two applications of GORDON'S PRUNING SEALER are recommended to seal small holes and cracks on these surfaces.

LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants only that the composition of this product conforms to the guaranteed analysis given on the label, and that the product is reasonably suited for the labeled use when applied according to the directions on the label.

THE MANUFACTURER NEITHER MAKES NOR INTENDS ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE EXPRESSLY DISCLAIMED. This limited warranty does not extend to the use of the product inconsistent with label instructions, warnings or cautions, or to use of the product under abnormal conditions such as drought, excessive rainfall, tornadoes, hurricanes, etc. These factors are beyond the control of the manufacturer or seller. Any damages arising from a breach of the manufacturer's warranty shall be limited to direct damages, and shall not include indirect or consequential damages such as loss of profits or values, except as otherwise provided by law.

The terms of this Limited Warranty and Disclaimer cannot be varied by any written or verbal statements or agreements. No employee or agent of the seller is authorized to vary or exceed the terms of this Limited Warranty and Disclaimer in any manner.

687/1-2004

Distributed By



pbj/GORDON

CORPORATION

An Employee-Owned Company

1217 West 12th Street

Kansas City, Missouri 64101

www.pbjgordon.com